



wireless

data transmission

Features:

- 69/80 test locations in direct neighbourhood
- any number of measuring devices can be used for each workstation
- combination of 433/868 MHz & Bluetooth

bi-directional transmission path:

- transmission check
- display evaluation of the measured value on the transmitter

Feedback displayed on measuring equipment via colour code

- ○ radio path in order
- ● radio path disordered
- ○ ● measured value within tolerance
- ● ● measured value exterior tolerance



series F/B

433 / 868 MHz
Bluetooth



PC, Notebook, PDA



infra - DAT 2000 RC BD

ELIAS GmbH

Westring 303
D-44629 Herne
Telefon: +49 2323 925 501
Fax: +49 2323 925 502
E-Mail: info@elias-gmbh.de
Internet: www.elias-gmbh.de



standard

data transmission

USB:

- new software desktop easy to handle
- keyboard interface for transferring the measured value to any Windows (R) application
- power supply from PC
- large display of the measured values
- numerous formatting possibilities of the measured value
- easy replacement of the battery cover

Mitutoyo-Digimatic:

- compatible with all Mitutoyo-Digimatic devices
- possibility of external measuring value request
- possible connection to RS232 or USB by using an adaptor of **Mitutoyo Messgeräte GmbH**
- easy replacement of the battery cover



series F/B

6,01 mm

USB & Mitutoyo-Digimatic

PC, notebook,
data transmitter, data logger,
statistic mini processor

